

DESCRIPTION

Gulf Western Multi-Purpose DWF spray is a heavy duty water dispersant aerosol designed to displace moisture and lubricate, protect and start wet motors. The product is suitable to be used on most machinery parts, heavy duty engines and hobby engines. It is fast acting in displacing moisture from engines and motor parts and protects against corrosion. Gulf Western Multi-Purpose DWF spray also stops squeaks and loosens rust parts.

DIRECTIONS FOR USE

To enable Gulf Western Multi-Purpose DWF Spray to penetrate engine parts quickly and efficiently remove as much of the trapped dirt, dust and other contaminants from the surface by scraping or wiping with a rag. Repeat if necessary until surface is clean. Shake the can for about 1 minute to ensure uniformity of contents. For lubrication apply liberally onto the affected parts. To effect maximum penetration and corrosion protection apply additional coats and allow to stand for several minutes. Spray periodically as required.

USAGE

Under normal usage the Gulf Western Multi-Purpose DWF spray will provide up to 350 spray applications per 400 gram can. Usage will also be dependent on application technique.

WORKABILITY

When used to start up motors the Gulf Western Multi-Purpose DWF spray actives will immediately displace moisture from the surface. The product also contains special oils that quickly coat and seal the metal surface and prevent moisture from attacking and corroding the metal parts. The oils used also have lubricating properties that are very effective at silencing ongoing squeaks. Gulf Western Multi-Purpose DWF spray will displace moisture instantly from the surface and will maintain the surface moisture resistant for at least 10 hours. For very wet conditions and where the vehicle had traveled through puddles of water it may be necessary to saturate the surface with Gulf Western Multi-Purpose DWF spray for best results.

WARNING

Intentional misuse by deliberately concentrating or inhaling contents can be harmful or fatal. Keep in a cool dry place away from sun. Do not store above 50°C. Do not use near fire or naked flame. Do not incinerate this can even when empty. Dispose of waste residues and empty cans thoughtfully.

PROPELLANT

Hydrocarbon.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

400G - 64096

February 2022